

COMPATIBLE TO:

Astra Tech EV

ATE

3.0

3.6

4.2

4.8

5.4

Elos Accurate® Hybrid Base™ Engaging

Titanium Hybrid Base for screw-retained single restorations and cement-retained single and bridge restorations.

Torque Value: 25 Ncm



Gingival height	1.0 mm	1.0 mm	1.0 mm	1.0 mm	1.0 mm
Margin diameter	3.7 mm	3.7 mm	4.5 mm	4.5 mm	5.0 mm
Chimney height	3.0 mm	3.0 mm	3.0 mm	3.0 mm	3.0 mm

HBE-ATE30-1

HBE-ATE36-1

HBE-ATE42-1

HBE-ATE48-1

HBE-ATE54-1

Elos Accurate® Hybrid Base H™ Engaging

Titanium Hybrid Base for screw-retained single restorations and cement-retained single and bridge restorations.

Torque Value: 25 Ncm



Gingival height	1.0 mm	1.0 mm	1.0 mm
Margin diameter	3.7 mm	4.5 mm	4.5 mm
Chimney height	5.5 mm	3.0 mm	3.0 mm

HBE-ATE36H-1

HBE-ATE42H-1

HBE-ATE48H-1

Elos Accurate® Pre-Milled Blank

Pre-Milled Blank in titanium grade 5 for custom abutment restoration. For use with the Elos Accurate Pre-Milled Blank Holder.

Torque Value: 25 Ncm



PMB-ATE36-1

PMB-ATE42-1

PMB-ATE48-1

PMB-ATE54-1

Elos Prosthetic Screw

Prosthetic screw with M1.4, M1.6, M1.8 and M2.0 thread.

Screwdriver: 0.050" Hex screwdriver

Torque Value: 25 Ncm



AS-ATEM148POS

AS-ATEM168POS

AS-ATEM188POS

AS-ATEM208POS

AS-ATEM208POS

Elos Accurate® Hexalobular Prosthetic Screw

Prosthetic screw with M1.4, M1.6 and M1.8 thread.

Screwdriver: PS-AH18-1, PS-AH26-1 or PS-AH34-1, see last pages.

Torque Value: 25 Ncm



AS-ATEM1408A-1

AS-ATEM1608A-1

AS-ATEM1808A-1

AS-ATEM2008A-1

AS-ATEM2008A-1

COMPATIBLE TO:

Astra Tech UniAbutment EV/Multibase EV



UA 33°

4.5

Elos Accurate® Hybrid Base™ Non-Engaging

Titanium Hybrid Base screw for screw-retained bridge restorations.

Torque Value: 15 Ncm



Gingival height	1.0 mm	0.9 mm
Margin diameter	5.0 mm	5.0 mm
Chimney height	4.1 mm	4.1 mm

HBN-AUE33-1

HBN-MUA45-1

Elos Accurate® Hybrid Base H™ Non-Engaging

Titanium Hybrid Base for screw-retained bridge restorations.

Torque Value: 15 Ncm



Gingival height	0.3 mm	0.3 mm
Margin diameter	4.1 mm	5.0 mm
Chimney height	4.5 mm	4.5 mm

HBN-AUE33H-1

HBN-MUA45H-1

Elos Accurate® Hexalobular Prosthetic Screw

Prosthetic screw with M1.8 thread.

Screwdriver: PS-AH18-1, PS-AH26-1 or PS-AH34-1, *see last pages.*

Torque Value: 15 Ncm



AS-AUEM1805A-1

AS-MUAM1403A-1

Elos Prosthetic Screw

Prosthetic screw with M1.6, M2 and M2.5 thread

Screwdriver: Nobel Biocare Unigrip

Torque Value: 35 Ncm



AS-MUAM1403POS

COMPATIBLE TO:

Ankylos® Balance Base Abutment

DBA

Elos Accurate® Hybrid Base™ Non-Engaging

Titanium Hybrid Base for screw-retained bridge restorations.



Torque Value: 10 Ncm



Gingival height	0.6 mm
Margin diameter	5.0 mm
Chimney height	4.1 mm

HBN-DBA40-1

Elos Accurate® Hybrid Base H™ Non-Engaging

Titanium Hybrid Base for screw-retained bridge restorations.



Torque Value: 10 Ncm



Gingival height	0.3 mm
Margin diameter	4.4 mm
Chimney height	4.5 mm

HBN-DBA40H-1

Elos Prosthetic Screw

Prosthetic screw with M1.6 thread.

Screwdriver: 1.0 mm Hex screwdriver

Torque Value: 10 Ncm



AS-DBAM1605POS

Elos Accurate® Hexalobular Prosthetic Screw

Prosthetic screw with M1.6 thread.

Screwdriver: PS-AH18-1, PS-AH26-1 or PS-AH34-1, *see last pages.*



Torque Value: 10 Ncm



AS-DBAM1605A-1